

GUM TURPENTINE

Property & Usage



SumFlu™ Gum Turpentine is distilled and rectified from pine resin, which component is alpha pinene and beta pinene. It is a kind of natural essential oil, a mixture of various terpenoid and hydrocarbon with special chemical activity.

Usage in paint, synthetic camphor, terpineol, synthetic perfume, medicine production, synthetic resin, organic chemical industry, etc.

Technical Data Sheet (TDS-5100)

GUM TURPENTINE	SUPER GRADE
Color & appearance	clean, transparent
Specific gravity (20 / 4 deg C)	0.87 max.
Refractive index (20 deg C)	1.4650 - 1.4740
Initial distilling point (deg C)	150 min.
Distillate (below 170 deg C)	90% min.
Acid value (mgKOH/g)	0.5 max.

Package & Notes

Package 190kg net galvanized iron drum 175kg net galvanized iron drum 150kg net galvanized iron drum 20' ISO tank container	20'FCL load 15.2mt (80drums) 14mt (80drums) 18mt (120drums) 20mt about	
Structural - C₁₀H₁₆ 	CAS Number 8006-64-2 HS Code 38051000 UN NO. 1299	EC# (EINECS#) 232-350-7 Standard GB/T 12901-91 IMCO Class 3.3
Storage (Flash Point 35 deg C) In cool place, avoid fire and high temperature.		