# SAFETY DATA SHEET

## Distributor

SUMMIT TRADE PTE LTD 9/F Baiyun Riverscape Tower, 5 Xijiang 2nd Road, Wuzhou, Guangxi, China (543001) Last updated: January 2018

## Product identification

Product name: STYRENATED TERPENE RESIN CAS NO. unspecified Synonyms: resin ST80/ST100/ST120 Formula: macromolecule polymer Molecular weight: unspecified

#### Composition/information on ingredients Macromolecule polymer.

## **Hazards identification**

Routes of Entry: Inhalation: Yes Skin: Yes Ingestion: No Reports of Carcinogenicity: NTP: No IARC: No OSHA: No Health Hazards Acute and Chronic: Ingest/Skin Absorption/Skin Contact: No Eye-may cause irritate, experienced as stinging w/excess blinking & tear production. Redness & swelling of conjunctive may occur. Inhalation-:Short term harmful effect not expected

#### First aid measures

Eyes: immediately flush with copious amounts of water for at least 15 min.

Skin: immediately wash with soap and copious amounts of water.

Inhalation: remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Ingestion: wash out mouth with water provided person is conscious

## Fire fighting measures

Extinguishing media: water spray. Carbon dioxide, dry chemical powder or appropriate foam.

Fire fighting procedures: wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eves.

Unusual fire/explosion hazard: emits toxic fumes under fire con1ditions.

#### Accidental release measures

Spill release procedures: wear respirator, chemical safety goggles, rubber boots and heavy rubber gloves. Sweep up, place in a bag and hold for waste disposal. Avoid raising dust. Ventilate area and wash spill site after material pickup is complete.

## Handling and storage

Handling and storage precautions: avoid contact with eyes, skin and clothing. Avoid prolonged or repeated exposure. Avoid inhalation. Keep tightly closed. Store away from heat.

# **Exposure controls/Personal protection**

Respiratory protection: NIOSH/MSHA-approved respirator. Ventilation: mechanical exhaust required. Protective gloves: compatible chemical-resistant gloves. Eye protection: chemical safety glasses. Other protective equipment: safety shower and eye bath. Work hygienic practices: wash hands thoroughly after handling. Supplemental safety and health: none

## Physical and chemical properties

Appearance: yellow to red-brown transparent pieces Softening point (R&B, degree C): 80 - 120 Color (Gardner): 1 - 3 Acid value (mgKOH/g): 1 max Toluene-insoluble matter: 0.05% max.

#### Stability and reactivity data

Stability Indicator/Materials to Avoid: YES - Strong oxidizing agents, strong acids, strong alkalies, halofens, acyl halides. Prevent disperse of material in air to form dust-any finely divided org material in air can ignite dust explode

Hazardous Decomposition Products: burning/thermo decomposition can produce phenol, formaldehyde, CO(highly toxic if inhale) and/or CO2(sufficient conce act as asphyxiant).

## **Toxicological information**

Oral LD50 (formaldehyde): rat 100mg/kg Routes of exposure: the substance can be absorbed into the body by inhalation of fumes. Acute effects/symptoms: inhalation of dusts or fumes causes asthmatic reactions. Chronic effect: repeated or prolonged contact may cause skin sensitization. Repeated or prolonged inhalation exposure may cause asthma.

#### **Ecological information**

#### n/a

#### **Disposal considerations**

Waste disposal methods: dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local regulations.

## **Transport Information**

Non-hazardous for air, sea and road freight.

# **Regulatory Information**

Unspecified.

#### Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the data of its publication. The information given is designed only as a guidance for safe handling, use processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

