

PINE TAR OIL

Property & Usage

SumTac™ Pine Tar Oil is a botanical product with special odor obtained from the destructive distillation of pine wood or stump. It is a complicate mixture of kinds of phenols, fatty acids, volatile oils, terpenoid, etc. and has particular chemical characters.

Usage as efficient softening solvent in rubber & tyre industry, as preservative in wooden or other construction & medicine, as water-proof agent in paint & coating application, etc. and also used in pitch industry & mineral flotation.

Technical Data Sheet (TDS-9600)

PINE TAR OIL	EXPORT GRADE
Appearance & color	deep brown & viscous liquid
Viscosity S (100ml, 85 deg C)	150-250, 250-350, 350-450
Volatile content	6.5%, 6.0%, 5.5%
Specific gravity (D20/4)	0.96 - 1.06
Moisture content	0.5% max
Ash content	0.5% max
Mechanical Impurity content	0.3% max

Package & Notes

Package	20'FCL load	20'FCL palletized
200kg net galvanized iron drum	16mt (80drums)	16mt (80drums)
25kg net carton	21mt (840cartons)	18mt (720cartons)
HS code	CAS Number	EC# (EINECS)
38070000	8011-48-1/91995-59-4	232-374-8/295-321-8
UN No.	Storage (Flash Point 70-170 deg C)	
1993	In cool place, avoid fire and high temperature.	

