

PINE TAR OIL

Property & Usage

SumTac™ Pine Tar Oil is a botanical product with special odor obtained from the destructive distillation of pine wood or stump. It is a complicate mixture of kinds of phenols, fatty acids, volatile oils, terpenoid, etc. and has particular chemical characters.

Usage as efficient softening solvent in rubber & tyre industry, as preservative in wooden or other construction & medicine, as water-proof agent in paint & coating application, etc. and also used in pitch industry & mineral flotation.

Technical Data Sheet (TDS-9600)

| PINE TAR OIL | EXPORT GRADE |
|-------------------------------|-----------------------------|
| Appearance & color | deep brown & viscous liquid |
| Viscosity S (100ml, 85 deg C) | 150-250, 250-350, 350-450 |
| Volatile content | 6.5%, 6.0%, 5.5% |
| Specific gravity (D20/4) | 0.96 - 1.06 |
| Moisture content | 0.5% max |
| Ash content | 0.5% max |
| Mechanical Impurity content | 0.3% max |

Package & Notes

| | | |
|--------------------------------|---|--------------------------|
| Package | 20'FCL load | 20'FCL palletized |
| 200kg net galvanized iron drum | 16mt (80drums) | 16mt (80drums) |
| 25kg net carton | 21mt (840cartons) | 18mt (720cartons) |
| HS CODE | CAS Number | EC# (EINECS) |
| 38070000 | 8011-48-1/91995-59-4 | 232-374-8/295-321-8 |
| UN No. | Storage (Flash Point 70-170 deg C) | |
| 1993 | In cool place, avoid fire and high temperature. | |

